



## PAINT EMULSIONS

### Styrene Acrylic Emulsions

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 1245	45 +/-1 %	10-35 poise	8-10	200C	Low cost Paint Emulsion & as a Cement Primer
ADICRYL 1250	50 +/-1 %	5-15 poise	8-10	180C	For Quality Emulsion Paints for High Gloss & constructions
ADICRYL 1250 M	50 +/-1 %	0.5-5 poise	0.5-10	100C	For Superior quality Emulsion Paints

### Pure Acrylic Emulsions

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 2250	50 +/-1 %	50-300 cps	8-10	170C	} For High Quality Emulsion Paints with superior Sheen and Gloss for Exterior and Interior Applications
ADICRYL 2250 M	50 +/-1 %	10-300 cps	7-10	180C	
ADICRYL 2255	55 +/-1 %	5-15 poise	8-10	160C	

### Vinyl Acetate Acrylic Co-Polymer

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 3250	55 +/-1 %	10-40 poise	4-6	100C	For Producing Superior Quality Interior Paint
ADICRYL 3255	55 +/-1 %	10-40 poise	4-6	100C	For Producing Superior Quality Interior Paint
ADICRYL 3255 V	55 +/-1 %	10-30 poise	4-6	120C	Can be used to make Alkali resistant Emulsion Paint with Good Scrub resistance

### Polymer Additives for Paint

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 4228	29 +/-1 %	0.2-1	2-4	---	Used in Textured Paint & Construction Chemicals as thickener in water-based
ADICRYL 4230	30 +/-1 %	1-5 poise	8-10	---	Dispersion of inorganic pigments for paints and paper coatings
ADICRYL 4244	22 +/-1 %	150-250 cps	8-11	---	As thickener for water-based paints and water-based systems

## STICKER ADHESIVES

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 5255	55 +/-1 %	40-60 poise	5-6	---	Formulated for PSA labels / Stickers on high speed contineous coating machines For Pressure sentitive adhesive labels, stock label manufacturing, Bindis etc.
ADICRYL 5255 V	55 +/-1 %	50-90 poise	5-6	---	
ADICRYL 5255 E	52.5 +/-1 %			---	

## LAMINATION ADHESIVES

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 6245	44 +/-1 %	40-60 poise	4-6	---	Cheaper grade lamination adhesives for BOPP / PVC to paper board & craft paper. } cheaper adhesives for superior quality BOPP / PVC/ PET film and printed paper / board laminations.suitable for lamination on craft paper
ADICRYL 6250	50 +/-1 %	30-50 poise	4-6	---	
ADICRYL 6255	55 +/-1 %	30-60 poise	4-6	---	
ADICRYL 6240	40 +/-1 %			---	

## TAPE ADHESIVE

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 7255	55 +/-1 %	upto 1.5 poise	7-9	---	Used for BOPP self adhesive tape & other related pressure sentitive applications

## CONSTRUCTION CHEMICALS

### Water proofing & other chemicals

	<u>Solid Content</u>	<u>Viscosity</u>	<u>PH</u>	<u>Mfft</u>	<u>APPLICATION</u>
ADICRYL 8250	50 +/-1 %		7-9	---	Water proofing for flexible cementitious coating
ADICRYL 8247	47 +/-1 %	0.5-5 poise	8-9	---	Cement compatible Styrene Acrylic